

# 3D-LT BEVEL HEAD



## Fully automatic plasma beveling in simplified design

The 3D-LT Bevel Head offers fully automatic plasma beveling in a simplified design. The "Patent Pending" 3D-LT Bevel Head uses a unique drive system and sensor ring design to provide unlimited head rotation, without electrical slip rings, while providing remote mounting of servo motors and sensor components. This design provides tilt and rotation movements about the plasma focal point, with two axis transformations, to provide more intuitive movements and a theoretical reductions in bevel angle error.

## Features & Benefits

- **Initial Height Sensor**  
Has a fully integrated initial height sensing using ohmic contact
- **Real time arc voltage height control**  
With arc voltage tracking within 0.1 arc volts
- **Automatic kerf detection technology**  
Eliminates the need to lock out the height control when crossing the kerf or cornering
- **Height Control Process**  
Real time monitoring of height control process parameters
- **Fully enclosed cable carrier**  
Protects plasma cables, hoses and wiring
- **Manual positioning**  
capabilities for lift, tilt, and rotate axis





### 360° Continuous Rotation

Accuracy Height Control	± .004 inches
Accuracy Tilt	± 0.5°
Accuracy Rotation	± 0.5°
Overall Accuracy	± 0.5°
Repeatability	± 0.25°

SPECIFICATIONS	
Contour Cutting- Capable of Beveling angles to:	+50° to -50°
Rotation	360° Continuous
Tilt Speed	20 RPM
Rotation Speed	60 RPM
Height Control	Sensor THC
Compatible Machine(s)	Versagraph Extreme or Mastergraph EX2 Series
Plasma System	High-Density Plasma System (rated for bevel cutting mild steel 1/4" to 2" thick)
Bevel Types	A, V, X, Top Y, Bottom Y & K



### Versagraph Extreme

Options shown: operator chair, cutting table, 3D-LT Bevel head and two oxy-fuel cutting stations

The tilt axis is capable of producing +/- 50 degree bevel angles at a speed of 20 RPM. The rotation axis can continually rotate at a speed of 60 RPM. The speed and smoothness of the coordinated motion can produce high quality beveled holes and small corner loops, to minimize material waste. Standard features included with the 3D-LT Bevel Head include, fully integrated height control, automatic kerf detection and torch collision protection.

**Koike Aronson, Inc.**

P.O. Box 307, Arcade, New York 14009  
 Phone (585) 492-2400 Fax (585) 457-3517  
[www.koike.com](http://www.koike.com)

ISO 9001:2008  
 BUREAU VERITAS  
 Certification



**3D-LT BEVEL HEAD 01/15 KENG**